

## Installation Instructions for Hella LED/CELIS Tailamp Upgrade Kit For Dodge Ram 2005-2008 Models

1. Park the vehicle in a well lit, secure area.
2. Disconnect and protect the negative battery cable.
3. Lower the tailgate to find and remove the two screws that hold the OE tail lamp assembly to the side of the truck's bed. Once the screws have been removed, set them aside to be re-used on the new Hella LED Tail Lamps.
4. **Gently pull** the outer side of the OE tail lamp assembly back far enough to unsnap the two ball studs on the outer side of the OE tail lamp housing from the two plastic grommet clips that secure it to the truck's bed.
5. Pull the OE tail lamp assembly back from the truck far enough to be able to disconnect the two wiring harness connectors from the two bulb sockets on the rear of the tail lamp housing.
6. Completely remove the OE tail lamp assembly from the opening of the truck's bed. Repeat this process for both sides. Place the OE Tail Lamps in a safe, out of the way place.
7. Remove the plastic grommet clips from the fender (your Hella Lights are supplied with new ones)
8. Install the new plastic grommet clips supplied with your Hella lights.
9. Remove the OE bulbs from their bulb sockets (except reverse bulb) and put in a safe place.
10. Insert the terminals from the Hella LED Tail Lamps into the OE bulb sockets on the vehicle.
11. Install the OE bulb sockets into the Hella LED Tail lamps and gently twist them until they are locked into place.
12. Slide the Hella LED Tail Lamp Assembly into the fender of truck.
13. Place the two original mounting screws into the holes on the Hella LED Tail Lamp assembly and attach the light assembly to the truck snugly. **Do not tighten all the way yet!**
14. Adjust the fit of the assemblies and then perform a final tightening of the mounting screws.
15. **Test lamps for all functions before operating vehicle.**

NOTE: The fitment of these lights will vary from truck to truck. Factors relating to age of truck, miles of truck, accident repairs, and general build of truck will produce a wide range of results. Any of these factors may cause differences in the fitment of the lights.

**Hella, Inc.**  
201 Kelly Drive  
Peachtree City, GA 30269  
877.224.3552  
hella.faq@hella.com  
[www.myhellalights.com](http://www.myhellalights.com)



© Hella, Inc.  
05/2009